

JAPANESE PATENT OFFICE
PATENT JOURNAL
KOKAI PATENT APPLICATION NO. HEI 9[1997]-17913

Technical Disclosure Section

Int. Cl. ⁶ :	H 01 L	23/28 21/56 25/00
	H 01 L	23/28 21/56 25/00
Application No.:	Hei 7[1995]-163389	
Application Date:	June 29, 1995	
Publication Date:	January 17, 1997	
No. of Claims:	2(Total of 8 pages; OL)	
Examination Request:	Not requested	

ELECTRONIC CIRCUIT DEVICE

Inventors:	Takashi Setani Toshiba Corp., Seito Technical Training Center 33 Shinyonego-cho, Yonego-ku Yokohama-shi, Kanagawa-ken
	Santaro Shimizu Toshiba Corp., Seito Technical Training Center

33 Shinyonego-cho,
Yonego-ku Yokohama-shi,
Kanagawa-ken

Toshiaki Uchida
Toshiba Corp.,
Seito Technical
Training Center
33 Shinyonego-cho,
Yonego-ku Yokohama-shi,
Kanagawa-ken

Takashi Aiwa
Toshiba Corp.,
Seito Technical
Training Center
33 Shinyonego-cho,
Yonego-ku Yokohama-shi,
Kanagawa-ken

Applicant:

000003078
Toshiba Corp.
72 Horikawa-cho,
Shiawase-ku
Kawasaki-shi,
Kanagawa-ken

Agent:

Takahiko Suzue,
patent attorney

[There are no amendments to this patent.]


Abstract

Purpose

The present invention offers an electronic circuit device that is able to mount electronic parts such as LSI and passive chip parts on an electronic circuit substrate at high density (parts interval 0.3-5 mm) and with high reliability.

Constitution

This is an electronic circuit device having a wiring substrate, a semiconductor element mounted on this substrate by means of bumps, and passive element parts that are adjacent to this semiconductor element with a parts interval of 5 mm or less and that are mounted on said substrate by means of an electroconductive connecting material, and resin is arranged between said substrate and the semiconductor element and on the periphery of the semiconductor element. It is characterized in that the resin arranged on the periphery of said semiconductor element is arranged separated from the electroconductive connecting material that extends from the surface of the substrate of the resin and that mounts the passive element parts that are contiguous with said semiconductor element on the substrate.



Claim

1. An electronic circuit device having a wiring substrate, a semiconductor element mounted on this substrate by means of bumps, and passive element parts that are adjacent to this semiconductor element with a parts interval of 5 mm or less and that are mounted on said substrate by means of an electroconductive connecting material, and resin is arranged between said substrate and the semiconductor element and on the periphery of the semiconductor element,

characterized in that the resin arranged on the periphery of said semiconductor element is arranged separated from the electroconductive connecting material that extends from the surface of the substrate to the surface of the resin and that mounts the passive element parts that are contiguous with said semiconductor element on the substrate.

2. The electronic circuit device of Claim 1, characterized in that said wiring substrate is made from a resin material.

* * *